

Appendix B: Master Transportation Plan Summary Table

R=Required (Minimum Condition) ●=As Approved by Public Works Parks & Recreation Department -=Not Recommended
 Δ=Refer to Master Bicycle & Trails Plan *=Refer to RTC Transit Guide & System Map

			Compact Complete Communities	Suburban High Density High Intensity	Suburban Low Density Low-Medium Intensity	Residential Low-Medium Density Low Intensity	Residential Low Density Low Intensity	
Minor Collector	Inside ROW	Roadway	Expected ADT	≤ 10k	≤ 10k	≤ 10k	≤ 10k	≤ 10k
			Minimum Width	94 ft.	84 ft.	82 ft.	82 ft.	76 ft.
			Dedicated Width (back-of-curb to back-of-curb)	60 ft.	50 ft.	50 ft.	50 ft.	50 ft.
			Travel Lanes	2	2	2	2	2
			Lane Width	11 ft.	11 ft.	11 ft.	11 ft.	11 ft.
			Curb & Pan	2 ft.	2 ft.	2 ft.	2 ft.	2 ft.
			On-Street Parking	6 ft.	6 ft.	6 ft.	6 ft.	6 ft.
			Dedicated Transit Facilities	*	*	*	*	*
	Bicycle	Minimum Width	≥ 6 ft.	≥ 6 ft.	≥ 6 ft.	≥ 6 ft.	≥ 6 ft.	
		Buffered Bike Lane	●	●	●	●	●	
		Painted Bike Lane	R	R	R	R	R	
		Marked Shared Lane	●	-	-	●	●	
	Center	Minimum Width	10 ft.	0 ft.	0 ft.	0 ft.	0 ft.	
		Raised Median	●	●	●	●	●	
		Painted Median	●	●	●	●	●	
	Outside ROW	Pedestrian & Amenity	Minimum Width	≥ 17 ft.	≥ 17 ft.	≥ 16 ft.	≥ 16 ft.	≥ 16 ft.
			Walkway Width	≥ 8 ft.	≥ 8 ft.	≥ 6 ft.	≥ 6 ft.	≥ 6 ft.
			Amenity/Planting Width	≥ 9 ft.	≥ 9 ft.	≥ 10 ft.	≥ 10 ft.	≥ 10 ft.
			Detached Multi-Use Path	Δ	Δ	Δ	Δ	Δ

Appendix B: Master Transportation Plan Summary Table

R=Required (Minimum Condition) ●=As Approved by Public Works Parks & Recreation Department -=Not Recommended
 Δ=Refer to Master Bicycle & Trails Plan *=Refer to RTC Transit Guide & System Map

			Compact Complete Communities	Suburban High Density High Intensity	Suburban Low Density Low-Medium Intensity	Residential Low-Medium Density Low Intensity	Residential Low Density Low Intensity	
Major Collector	Inside ROW	Roadway	Expected ADT	10k – 25 k	10k – 25 k	10k – 25 k	10k – 25 k	10k – 25 k
			Minimum Width	130 ft.	137 ft.	133 ft.	126 ft.	126 ft.
			Dedicated Width (back-of-curb to back-of-curb)	84 ft.	91 ft.	91 ft.	84 ft.	84 ft.
			Travel Lanes	4	4	4	4	4
			Lane Width	11 ft.	11 ft.	11 ft.	11 ft.	11 ft.
			Curb & Pan	2 ft.	2 ft.	2 ft.	2 ft.	2 ft.
			On-Street Parking	6 ft.	7.5 ft.	7.5 ft.	6 ft.	6 ft.
			Dedicated Transit Facilities	*	*	*	*	*
		Bicycle	Minimum Width	≥ 6 ft.	≥ 8 ft.	≥ 8 ft.	≥ 6 ft.	≥ 6 ft.
			Buffered Bike Lane	●	R	R	●	●
	Painted Bike Lane		R	-	●	R	R	
	Marked Shared Lane		-	-	-	-	-	
	Center	Minimum Width	12 ft.	12 ft.	12 ft.	12 ft.	12 ft.	
		Raised Median	R	R	R	R	R	
		Painted Median	●	●	●	●	●	
	Outside ROW	Pedestrian & Amenity	Minimum Width	≥ 23 ft.	≥ 23 ft.	≥ 21 ft.	≥ 21 ft.	≥ 21 ft.
			Walkway Width	≥ 8 ft.	≥ 8 ft.	≥ 6 ft.	≥ 6 ft.	≥ 6 ft.
			Amenity/Planting Width	≥ 15 ft.	≥ 15 ft.	≥ 15 ft.	≥ 15 ft.	≥ 15 ft.
			Detached Multi-Use Path	Δ	Δ	Δ	Δ	Δ

Appendix B: Master Transportation Plan Summary Table

R=Required (Minimum Condition) ●=As Approved by Public Works Parks & Recreation Department -=Not Recommended

△=Refer to Master Bicycle & Trails Plan *=Refer to RTC Transit Guide & System Map

			Compact Complete Communities	Suburban High Density High Intensity	Suburban Low Density Low-Medium Intensity	Residential Low-Medium Density Low Intensity	Residential Low Density Low Intensity
Minor Arterial	Inside ROW	Roadway	Expected ADT	25k – 40 k		25k – 40k	
			Minimum Width	154 ft.		158 ft.	
			Dedicated Width (back-of-curb to back-of-curb)	98 ft.		98 ft.	
			Travel Lanes	6		6	
			Lane Width	11 ft.		11 ft.	
			Curb & Pan	2 ft.		2 ft.	
			On-Street Parking	-		-	
			Dedicated Transit Facilities	*		*	
	Bicycle	Minimum Width	≥ 8 ft.		≥ 8 ft.		
		Buffered Bike Lane	R		R		
		Painted Bike Lane	-		-		
		Marked Shared Lane	-		-		
	Center	Minimum Width	12 ft.		12 ft.		
		Raised Median	R		R		
		Painted Median	●		●		
	Outside ROW	Pedestrian & Amenity	Minimum Width	≥ 28 ft.		≥ 30 ft.	
			Walkway Width	≥ 8 ft.		≥ 10 ft.	
			Amenity/Planting Width	≥ 20 ft.		≥ 20 ft.	
			Detached Multi-Use Path	△		△	

Appendix B: Master Transportation Plan Summary Table

R=Required (Minimum Condition) ●=As Approved by Public Works Parks & Recreation Department -=Not Recommended

△=Refer to Master Bicycle & Trails Plan *=Refer to RTC Transit Guide & System Map

			Compact Complete Communities	Suburban High Density High Intensity	Suburban Low Density Low-Medium Intensity	Residential Low-Medium Density Low Intensity	Residential Low Density Low Intensity
Major Arterial	Inside ROW	Roadway	Expected ADT	≥ 40 ft.		≥ 40 ft.	
			Minimum Width	154 ft.		162 ft.	
			Dedicated Width (back-of-curb to back-of-curb)	122 ft.		122 ft.	
			Travel Lanes	8		8	
			Lane Width	11 ft.		11 ft.	
			Curb & Pan	2 ft.		2 ft.	
			On-Street Parking	-		-	
			Dedicated Transit Facilities	*		*	
		Bicycle	Minimum Width	≥ 8 ft.		≥ 8 ft.	
			Buffered Bike Lane	R		R	
	Painted Bike Lane		-		-		
	Marked Shared Lane		-		-		
	Center	Minimum Width	14 ft.		14 ft.		
		Raised Median	R		R		
		Painted Median	●		●		
	Outside ROW	Pedestrian & Amenity	Minimum Width	≥ 16 ft.		≥ 20 ft.	
			Walkway Width	≥ 8 ft.		≥ 10 ft.	
			Amenity/Planting Width	≥ 8 ft.		≥ 10 ft.	
			Detached Multi-Use Path	△		△	